

Supplier	TOSHIBA CARRIER CORPORATION	
Innengerät	RAS-B07J2KVG-E	
Außengerät	RAS-07J2AVG-E	

Sound power level

Innengerät (kühlen)	dB	53
Außengerät (kühlen)	dB	61
Innengerät (heizen)	dB	53
Außengerät (heizen)	dB	63

Kältemittel

Typ	R32	
Global Warming Potential	kgCO ₂ eq	675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class	A++	
Design load (Pdesignc)	kW	2.0
Saisonale Effizienz (SEER)	6.10	
Saisonaler Energieverbrauch (QCE)	kWh/annum	115

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A+	A+	x
Design load (Pdesignh)	kW	2.0	1.1	x,x
Saisonale Effizienz (SCOP)		4.00	4.30	x,xx
Saisonaler Energieverbrauch (Q _{HE})	kWh/annum	699	354	x
Back up Heizleistung	kW	0.00		
Heizleistung bei einer Innenraumtemperatur von 20°C und Außentemperatur Tj.				
Tj= -7°C (Pdh)	kW	1.77	-	x,xx
Tj= 2°C (Pdh)	kW	1.08	1.08	x,xx
Tj= 7°C (Pdh)	kW	0.69	0.69	x,xx
Tj= 12°C (Pdh)	kW	0.68	0.68	x,xx
Tj=bivalent temperature (Pdh)	kW	1.77	1.08	x,xx
Tj=Betriebsgrenze (Pdh)	kW	2.68	2.68	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx