Lighting technology		[HL□/LFL T5 HF□/ LFL T5 HO□/CFni□/other FL□ /HPS□/MH□/other HID□ /LED■/OLED□/mixed□ /other□]	Non-directional or directional:	[NDLS■/DLS□]
Mains or non-mains		[MLS■/NMLS□]	Connected light source(CLS)	[yes■/no□]
Colour-tuneable light source		[yes□/no■]	Envelope	[no■/second□/non-clear□]
High luminance light source		[yes□/no■]		
Anti-glare shield		[yes□/no■]	Dimmable	[Yes■/only□/ with specific dimmers/no□]
On-mode power, expressed in W		9 W	EEI class	[A□/B□/C□/D□/E□/F■/G□][d]
Useful luminous flux (lm)& Beam angle correspondence		806 lm in [sphere■/wide cone□/narrow cone□]	Correlated colour temperature type	2500-6500K single
On-mode power (W)		9.0W	**Standby power (W)**	0.5W
Networked standby power for CLS (W)		0.50W	**Colour rendering index**	80
Outer dimensions without separate control gear, lighting control parts and non-lighting	Height	60mm	**Chromaticity coordinates (x and y)**	0.459,0.418
	Width	60mm		

control parts, if any (millimetre)	Depth	115mm		
R9 Colour rendering index		2	**Survival factor**	1
Lumen maintenance factor		0.93	**Colour consistency in McAdam ellipses**	5
displacement factor (cos φ1)		0.9	**Replacement claim (W)**	60
Flicker metric (Pst LM)		0.1	**Stroboscopic effect metric (SVM)**	0.1